

DRYLOK® Concrete Cleaner & Degreaser

MANUFACTURER

UNITED GILSONITE LABORATORIES

MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • **FAX:** 1-570-969-7634

www.ugl.com



PRODUCT DESCRIPTION

UGL DRYLOK Cleaner & Degreaser is specially formulated to clean and degrease concrete and masonry surfaces in one easy step. Because of its deep cleaning formula, UGL Concrete Cleaner & Degreaser cuts through grease, oil and dirt. Not for use on asphalt or painted surfaces.

- Cuts through the toughest dirt, oil & grease stains
- Perfect for preparing concrete floors to be painted

BASIC USES

UGL Concrete Cleaner & Degreaser is ideal for cleaning concrete walkways, patios, garage floors, basements, concrete driveways, carports, pool areas, concrete tennis courts, and brick, stucco or concrete walls.

TECHNICAL DATA

COMPOSITION:

N/A

SHEEN:

N/A

% WEIGHT SOLIDS:

19-21%

% VOLUME SOLIDS:

19-21%

DENSITY (LBS./US GAL.):

8.0±0.2

VISCOSITY:

N/A

pH:

N/A

COLORS:

N/A

ACTIVE TIME:

• 5-10 Minutes

CLEAN UP:

Soap and water

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

COVERAGE (SQ. FT./US GAL.):

• 150 sq. ft./gal.

Note: Actual coverage will vary depending upon application method, surface texture and porosity.

RECOMMENDED FILM THICKNESS/COAT:

N/A

FLASH POINT:

N/A

SHELF LIFE:

N/A

FREEZE/THAW:

N/A

CONTAINER SIZES:

One quart (US) and one gallon (US) containers

VOC

N/A

TINTING

N/A

SURFACE PREPARATION

UGL DRYLOK Concrete Cleaner & Degreaser should be applied to bare concrete, masonry or stucco.

Surfaces to be cleaned must be free of standing water. Sweep or vacuum the surface.

WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC.

EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Wear eye protection and rubber gloves. Apply full strength. Do Not Thin. Pour, brush or spray UGL DRYLOK Concrete Cleaner & Degreaser on the area to be cleaned. Allow cleaner to remain on the surface for 5 minutes, then thoroughly flush with water. For tough stains apply the Cleaner & Degreaser, let it stand for 5-10 minutes, then scrub with a stiff brush or broom and rinse with water.

Avoid applying in direct sunlight or on excessively hot surfaces.

If after cleaning, surface is to be painted or stained, treat smooth concrete with DRYLOK Etch or muriatic acid, according to manufacturer's directions. A properly etched surface should look and feel slightly rough, like fine sandpaper. If surface remains smooth, repeat the etching procedure until the surface has the proper texture. Thoroughly rinse the surface with clean water.

NOTE: Allow etching solution to remain on the surface for at least 20 minutes. While etching, the concrete surface should bubble.



DRY TIME:
24 Hours



CLEAN-UP:
Soap and Water



COVERAGE:
1 Application



SPREAD RATE:
150 Sq. Ft./Gallon

If some areas do not, this indicates deep oil or grease stains requiring additional cleaning. Scrub these areas again with UGL DRYLOK Concrete Cleaner & Degreaser and repeat the etching procedure. Allow the surface to dry at least 24 hours before staining or painting.

CAUTION

Contains Petroleum Distillate. Keep away from heat and flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying.

If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection

(NIOSH/MSHA TC 23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin.

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

FIRST AID

EYES: Flush with water. Consult a physician if irritation persists..

SKIN: Wash affected areas with soap and water. Consult a physician if irritation persists.

INGESTION: Seek medical attention. If individual is drowsy or unconscious do not give anything by mouth. Place individual on the left side with head down. Contact a physician, medical facility or poison control center for advice about whether to induce vomiting.

INHALATION: Remove to fresh air.

For additional health and safety information please refer to the "Materials Safety Data Sheet".

WARRANTY

N/A

SPECIFICATION

N/A



Concrete Cleaner & Degreaser
1 QT. 4/Case22312
1 GAL. 2/Case22313

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.