

**DRYLOK® Concrete Patch**

**MANUFACTURER**

**UNITED GILSONITE LABORATORIES**

**MAILING:** P.O. Box 70, Scranton, Pennsylvania, 18501

**SHIPPING:** 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

**TOLL FREE:** 1-800-UGL-LABS (845-5227)

**PHONE:** 1-570-344-1202 • **FAX:** 1-570-969-7634

**www.ugl.com**



**PRODUCT DESCRIPTION**

DRYLOK Concrete Patch is an interior and exterior cement patching system. The special dry powder cement is fortified with a powdered bonding agent to improve masonry-to-masonry adhesion. Mixes easily with water. DRYLOK Concrete Patch provides superior adhesion to hairline cracks or large breaks. It is waterproof, self-curing and will not shrink after drying. DRYLOK Concrete Patch will not chip or crack like concrete.

- Combines durability of cement with working qualities of a bonding agent in an easy repair kit
- Will not shrink, crack or chip like masonry
- Superior adhesion to hairline cracks or large breaks

**BASIC USES**

Ideal for use to top weld, join or patch brick and mortar, masonry walls, masonry steps and cracks in masonry floors.

**LIMITATIONS**

Not for use in repairing cracks or holes in masonry where there is an active flow of water. To stop active flow of water use a hydraulic cement like DRYLOK Fast Plug.

**TECHNICAL DATA**

**COMPOSITION:**

Cement/sand ration 1 to 1

**SHEN:**

N/A

**% WEIGHT SOLIDS:**

100%

**% VOLUME SOLIDS:**

100%

**DENSITY (LBS./US GAL.):**

N/A

**VISCOSITY:**

N/A

**COLORS:**

- Gray

**SET TIME:**

- 24 hours

**Note:** Maximum cure and dry time will be prolonged when slightly humid and damp, cool conditions prevail.

**CLEAN UP:**

Soap and water

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**COVERAGE (SQ. FT./US GAL.):**

- 80 cu. in./6 lb.

**Note:** Actual coverage will vary depending upon application method, surface texture and porosity.

**RECOMMENDED FILM THICKNESS/COAT:**

N/A

**FLASH POINT:**

N/A

**SHELF LIFE:**

N/A

**FREEZE/THAW:**

N/A

**CONTAINER SIZES:**

Six pound (US), twelve pound (US) kit containers

**VOC**

N/A

**TINTING**

N/A

**SURFACE PREPARATION**

The area to be repaired must be clean and free from all dirt and loose material. DRYLOK Concrete Patch will not adhere to crumbly or powdery surfaces. If area to be patched has been washed, mop up excess water.

Mix DRYLOK Concrete Patch right in DRYLOK Concrete Patch container. Wear a dust mask to avoid breathing dry powder. Slowly add water to the special cement powder (1 part water to 3 parts cement for normal repairs) stirring constantly until the consistency is smooth. Adjust consistency if necessary by adding additional water or cement powder. To repair small cracks, mix to a thin consistency; for deep or wide repairs, use a heavy consistency.

**WARNING**

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**APPLICATION**

Wet surface to be patched with clean water. When repairing small cracks apply DRYLOK Concrete Patch with a stiff brush. After approximately 10 minutes, remove excess material by scraping with putty knife. For



**SET TIME:**  
24 Hours



**CLEAN-UP:**  
Soap and Water



**COVERAGE:**  
1 Application



**SPREAD RATE:**  
80 cu. in./6 lb.

deep or wide repairs apply patch with a putty knife or trowel.

DRYLOK Concrete Patch should be used within two hours after mixing. Even though DRYLOK Concrete Patch provides better adhesion than other types of repair materials, the reopening of patched areas due to settling and expansion or contraction can occur. Do not use in temperatures below 40°F. To strengthen the bond of DRYLOK Concrete Patch to difficult surfaces such as dense or slick concrete, coat surface with DRYLOK Latex Bonding Agent instead of water before patching. Apply DRYLOK Latex Bonding Agent by brush or spray. Wait for it to change from milky color to a clear glaze (approx. 30 minutes) before applying patch.

**CAUTION**

**CONTAINS PORTLAND CEMENT.**

Cancer Hazard. Contains crystalline silica which can cause cancer. Do not breathe dust. Wear dust mask or respirator when handling dry powder. Avoid eye contact or prolonged contact with skin. Wash thoroughly after handling.

First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush with plenty of water for at least 15 minutes. Consult a physician immediately.

Use with adequate ventilation.

Do not take internally. Close container after use.

KEEP OUT OF REACH OF CHILDREN

This product contains a chemical known to the State of California to cause cancer.

**FIRST AID**

**EYES:** Immediately flush eye throughly with

water, continue flushing eye for at least 15 minutes, including under lids, to remove all particles. Call a physician.

**SKIN:** Wash skin with cool water and pH – neutral soap or mild detergent. See a physician if irritation is present.

**INGESTION:** Do not induce vomiting. If conscious, drink plenty of water. Call a physician.

**INHALATION:** Remove to fresh air. If breathing is difficult, administer oxygen. If not breathing, give artificial respiration.

For additional health and safety information please refer to the "Safety Data Sheet".

**WARRANTY**

N/A.

**SPECIFICATION**

N/A



Concrete Patch – Gray  
6 LB. 2/Case .....22123  
12 LB. 1/Case .....22125

**DISCLAIMER:** This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.