



PRODUCT DATA SHEET

Publication Date: 8-31-20

DRYLOK® Concrete and Masonry Etch & Cleaner

PRODUCT DESCRIPTION

DRYLOK® Concrete and Masonry Etch & Cleaner is a liquid cleaner and etch solution that prepares interior and exterior concrete, stone, tile, galvanized surfaces, and brick before coating to achieve a proper bond. It removes efflorescence (salt-like deposits) and excess mortar.

- Prepares smooth concrete to maximize adhesion and penetration for coatings and paints
- Removes efflorescence
- Cleans mortar from brick and tile
- Conditions galvanized surfaces for painting
- Self neutralizing
- No harmful fumes, safer than muriatic acid

BASIC USES

Cleans and etches concrete, stone, tile galvanized metal and brick.

TECHNICAL DATA

COMPOSITION: Acid solution

SHEEN: N/A

% WEIGHT SOLIDS: N/A

% VOLUME SOLIDS: N/A

DENSITY (LBS./US GAL.): 8.38-8.43

VISCOSITY: N/A

pH: .30-0.35

COLORS: N/A

ACTIVE TIME: N/A

COVERAGE:

300-600 sq. ft./gal.

Note: Actual coverage will vary depending upon application method, surface texture, and porosity.



COVERAGE

300-600 sq. ft./gal.



ACTIVE TIME

Until Foaming Action Stops



CLEAN-UP

Water

Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

RECOMMENDED FILM THICKNESS/COAT: N/A

FLASH POINT: N/A

SHELF LIFE: N/A

FREEZE/THAW: Protect from freezing

CONTAINER SIZES: One gallon (US) container

VOC

N/A

TINTING

N/A

LIMITATIONS

Do not apply to concrete that has already been sealed, painted, or stained. Additional applications may be required when used as a concrete etching compound or when conditions of excessive efflorescence buildup exist.

SURFACE PREPARATION

Surface must be clean and free from dirt, dust.

APPLICATION

Apply when air and surface temperature is above 50°F (10°C). Wear safety goggles with side shields, rubber gloves, and protective footwear. Surfaces to be treated should be slightly damp. For vertical surfaces apply DRYLOK® Concrete and Masonry Etch & Cleaner with an acid resistant sprayer or a synthetic brush. For horizontal surfaces apply DRYLOK® Concrete and Masonry Etch & Cleaner using a plastic garden watering can with a sprinkling head or an acid resistant sprayer. DO NOT pour onto one spot and brush out over surface. Using a stiff bristle brush or broom, scrub DRYLOK® Concrete and Masonry Etch & Cleaner into surface until foaming action stops. If the liquid etch does not foam, the concrete has been sealed and sealer must be removed using a suitable chemical remover or surface abradar. Triple rinse surface with a strong stream of water, scrubbing while rinsing to ensure removal of all etching material. When dry, check surface by applying a few drops of water. Water should penetrate quickly – if not re-apply DRYLOK® Concrete

and Masonry Etch & Cleaner to the affected area as described previously. Allow surface to dry thoroughly before applying paint or stain. A properly etched horizontal surface should look and feel like 120-grit medium sandpaper

CAUTION

Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

**KEEP OUT OF REACH OF CHILDREN.
DO NOT ALLOW TO FREEZE.
DO NOT TAKE INTERNALLY**

FIRST AID

EYES: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Do not apply any medicated agents except on the advice from a physician. Seek immediate medical attention/advice.

SKIN: Wash off immediately with plenty of water for at least 15 minutes. Take off contaminated clothing. Wash contaminated clothing before reuse. Wash with soap and water. Do not apply any medicated agents except on the advice from a physician. Get medical attention if necessary.

INGESTION: Rinse mouth. Do not induce vomiting without medical advice. Drink 2-3 large glasses of water. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. To ensure airway is open, position with head lower than body and transport immediately to a medical facility

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. Do NOT use mouth-to-mouth resuscitation. Call a physician if you feel unwell.

For additional health and safety information, please refer to the Safety Data Sheet (SDS).

DRYLOK® is a registered trademark of United Gilsonite Laboratories (UGL).

DRYLOK® CONCRETE AND MASONRY ETCH & CLEANER

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.

	CONTAINER	NUMBER/CASE	ORDER NUMBER
DRYLOK® Concrete and Masonry Etch & Cleaner	1 gallon	2/case	22413



1-800-845-5227 • Fax 1-570-969-7634 • www.UGL.com

Corporate Office: 1396 Jefferson Avenue, Dunmore, PA 18509

Mail to: P.O. Box 70, Scranton, PA 18501-0070

Plant Locations: Jacksonville, IL • Jackson, MS