

**DRYLOK® Non-Skid Texture Additive**

**MANUFACTURER**

**UNITED GILSONITE LABORATORIES**

**MAILING:** P.O. Box 70, Scranton, Pennsylvania, 18501

**SHIPPING:** 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

**TOLL FREE:** 1-800-UGL-LABS (845-5227)

**PHONE:** 1-570-344-1202 • **FAX:** 1-570-969-7634

**www.ugl.com**



**PRODUCT DESCRIPTION**

DRYLOK Non-Skid Texture Additive increases traction and helps prevent slipping and falling by providing a slip resistant coating. For use with DRYLOK E1 1-Part Epoxy Floor Paint and other oil, latex or epoxy floor paints. DRYLOK Non-Skid Texture Additive will not change the drying characteristics or film thickness recommendation of the paint that it is added to.

It will however alter the appearance of the surface by lowering the gloss due to the light scattering effect of the particles that will stick up out of the surface of the paint. DRYLOK Non-Skid Texture Additive contains natural pumice.

- Lightweight aggregate additive to paint, does not settle to bottom
- Increase traction and help prevent falls, accidents and injuries

**BASIC USES**

Use on garage floors, patios, stairs, basements, driveways, ramps and walkways.

**TECHNICAL DATA**

**COMPOSITION:**

powder

**SHEEN:**

N/A

**% WEIGHT SOLIDS:**

100%

**% VOLUME SOLIDS:**

100%

**DENSITY (LBS./US GAL.):**

19.6 ± 0.1

**VISCOSITY:**

N/A

**pH:**

N/A

**COLORS:**

- Off white

**DRY TIME:**

N/A

**CLEAN UP:**

Vacuum clean spillage. If sweeping, use a dust suppressant.

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**COVERAGE (OZ./US GAL.):**

- 2 oz.-4 oz./gal.

**Note:** Actual coverage will vary depending upon application method, surface texture and porosity.

**RECOMMENDED FILM THICKNESS/COAT:**

N/A

**FLASH POINT:**

N/A

**SHELF LIFE:**

N/A

**FREEZE/THAW:**

N/A

**CONTAINER SIZES:**

Four ounce (US) container

**VOC**

N/A

**TINTING**

N/A

**SURFACE PREPARATION**

Add 4 oz. bottle to 1 gallon of any oil, latex based or epoxy floor paint. Pour powder into paint and mix thoroughly.

For best results use a drill with a stirring blade. Stir thoroughly before and during application.

**WARNING**

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**APPLICATION**

N/A

**CAUTION**

Wear eye goggles to prevent eye irritation.

KEEP OUT OF REACH OF CHILDREN.

**FIRST AID**

**EYES:** Flush with copious amounts of clean water for 15 minutes. Consult a physician if irritation persists.

**SKIN:** None known.

**INGESTION:** Non-Hazardous

**INHALATION:** Blow nose, rinse mouth, drink water to clear throat. Move to fresh air.

For additional health and safety information please refer to the "Materials Safety Data Sheet".

**WARRANTY**



**DRY TIME:**

Varies on Usage



**CLEAN-UP:**

Vacuum if Spilled



**COVERAGE:**

Varies on Usage



**SPREAD RATE:**

Varies on Usage

N/A

**SPECIFICATION**

N/A



**Non-Skid Texture Additive**  
4 OZ. 6/Case .....01804

**DISCLAIMER:** This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label. **LR314**