

DRYLOK® Pourable Crack Filler

MANUFACTURER

UNITED GILSONITE LABORATORIES

MAILING: P.O. Box 70, Scranton, Pennsylvania, 18501

SHIPPING: 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

TOLL FREE: 1-800-UGL-LABS (845-5227)

PHONE: 1-570-344-1202 • FAX: 1-570-969-7634

www.ugl.com



PRODUCT DESCRIPTION

DRYLOK Pourable Masonry Crack Filler is formulated to fill and seal cracks on interior and exterior concrete and masonry surfaces. Reduces radon gas penetration. Dries to the color of concrete.

- Seals and fills cracks in concrete and masonry
- Excellent adhesion to damp surfaces
- Paintable
- Indoor/outdoor use
- Dries to the color of concrete
- Reduces radon gas penetration

BASIC USES

Ideal for interior and exterior concrete and masonry sidewalks, walkways, steps, patios, garage floors, etc.

TECHNICAL DATA

COMPOSITION:

N/A

SHEEN:

N/A

% WEIGHT SOLIDS:

85%

% VOLUME SOLIDS:

72%

DENSITY (LBS./US GAL.):

N/A

VISCOSITY:

N/A

COLORS:

- Gray

SET TIME:

- 12 Hours

Note: Maximum cure and dry time will be prolonged when slightly humid or when damp, cool conditions prevail.

CLEAN UP:

Soap and water

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

COVERAGE (SQ. FT./US GAL.):

- N/A

Note: Actual coverage will vary depending upon application method, surface texture and porosity.

RECOMMENDED FILM THICKNESS/COAT:

FLASH POINT:

N/A

SHELF LIFE:

N/A

FREEZE/THAW:

N/A

CONTAINER SIZES:

One quart (US) container

VOC

Does not exceed 40 g/L

TINTING

N/A

SURFACE PREPARATION

Apply when air and surface temperatures are a minimum of 50°F (10°C). Crack must be free from frost, dust, dirt, oil and particles. Wire brushing and hosing facilitates cleaning. Remove excess moisture before filling the crack. Do not apply if rain is expected within 24 hours. SHAKE WELL BEFORE USING. Use only when cracks are 1/2" wide or less.

WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE

SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Remove the red cap. Cut the tip of the spout to a size slightly smaller than the width of the crack. Squeeze DRYLOK Pourable Masonry Crack Filler tightly into the crack, over-filling slightly to allow for shrinkage. Smooth patched area with a putty knife. Replace the cap after use.

VENTILATION

Use only with adequate ventilation.

CAUTION

Cancer hazard: Contains Crystalline Silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust generated from sanding surfaces, grinding or spray mists.

Use only with adequate ventilation. Do not breathe dust. Avoid exposure to dust by wearing an appropriate (NIOSH approved) particulate respirator during sanding. Follow respirator manufacturer's directions for respirator use. Close container after each use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air.



SET TIME:
12 Hours



CLEAN-UP:
Soap and Water



COVERAGE:
Varies on Application



SPREAD RATE:
Varies on Application

If continued difficulty is experienced, get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN.
DO NOT TAKE INTERNALLY.
KEEP FROM FREEZING.

This product contains a chemical known to the State of California to cause cancer.

If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulators.

FIRST AID

EYES: Flush eye thoroughly with water. See a physician if irritation persists.

SKIN: Wash affected area with soap and water. See a physician if irritation is present.

INGESTION: Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth. Place individual on the left side with head down. Contact a physician, medical facility or poison control center for advice about whether to induce vomiting.

INHALATION: Remove to fresh air.

For additional health and safety information please refer to the "Materials Safety Data Sheet".

WARRANTY

N/A

SPECIFICATION

N/A



Pourable Masonry Crack Filler – Gray
1 QT. 6/Case30512

DISCLAIMER: This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.