

# Oil Base DRYLOK® Masonry Waterproofer

## MANUFACTURER

### UNITED GILSONITE LABORATORIES

**MAILING:** P.O. Box 70, Scranton, Pennsylvania, 18501

**SHIPPING:** 1396 Jefferson Avenue, Dunmore, Pennsylvania, 18509

**TOLL FREE:** 1-800-UGL-LABS (845-5227)

**PHONE:** 1-570-344-1202 • **FAX:** 1-570-969-7634

**www.ugl.com**



## PRODUCT DESCRIPTION

Oil Base DRYLOK Masonry Waterproofer is the manageable way to solve water seepage problems. Reduces radon gas penetration by reducing vapor transfer.

- Guaranteed to stop water
- No pre-mixing or pre-wetting
- Resists 10 psi, equivalent to a wall of water 22 ft. high
- Fully transferable 10 year warranty
- White is tintable

## BASIC USES

Formulated for waterproofing all interior, exterior, above or below grade masonry walls, cinder and concrete blocks, stucco and brick, retaining walls, fish ponds, birdbaths, basement walls and foundations.

## TECHNICAL DATA

### COMPOSITION:

Oil base

### SHEEN:

Flat

### % WEIGHT SOLIDS:

75-77%

### % VOLUME SOLIDS:

48-50%

### DENSITY (LBS./US GAL.):

13 ± 0.25

### VISCOSITY:

100-104 KU @77°F

### COLORS:

- White – ready mixed formula
- 2 ready mixed colors

### DRY TIME:

- 12-24 hours
- To recoat: 12 hours

**Note:** Maximum cure and dry time will

be prolonged when slightly humid and/or damp, cool conditions prevail.

### CLEAN UP:

Paint thinner

Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

### COVERAGE (SQ. FT./US GAL.):

• Smooth surfaces: 100 sq. ft./gal. for first coat and 100-125 sq. ft./gal. for succeeding coats

• Rough surfaces: 75 sq. ft./gal. for first coat and 125 sq. ft./gal. for succeeding coats

**Note:** Actual coverage will vary depending upon application method, surface texture and porosity.

### RECOMMENDED FILM THICKNESS/COAT:

13-21 Wet mils/coat

### FLASH POINT:

104°F

### SHELF LIFE:

N/A

### FREEZE/THAW:

Stable, store indoors

### CONTAINER SIZES:

One gallon (US) and five gallon (US) containers

### VOC

Does not exceed 400 g/L

### TINTING

Tint to light shades with alkali-proof universal tinting colors. Do not use more than 2 fl. oz. of colorant per gallon.

### SURFACE PREPARATION

Masonry surfaces must be clean and free from

dirt, dust, grease, oil, form release compound, frost and paint. Patch all holes or cracks with DRYLOK FAST PLUG®, a fast setting hydraulic cement, and smooth the patch evenly with the surface around it. Check the joint where the floor and wall meet and fill any breaks with DRYLOK FAST PLUG®.

**EFFLORESCENCE**, a white, powdery, crystal-like deposit visible on the masonry surface must be removed.

DRYLOK ETCH or muriatic acid, used according to manufacturer's directions, are effective efflorescence removal agents. All masonry surfaces are subject to occurrences of efflorescence.

DRYLOK may be applied on slightly damp surfaces but best results are obtained when applied on dry surfaces. Not warranted when used over previously painted or horizontal surfaces.

### WARNING

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).


### APPLICATION

STIR THOROUGHLY BEFORE AND DURING APPLICATION. DO NOT THIN.



#### DRY TIME:

12-24 hours  
Recoat 12 Hours



#### CLEAN-UP:

Paint Thinner



#### COVERAGE:

2 Coats Minimum



#### SPREAD RATE:

100 Sq. Ft./Gallon

Paint only when air and surface temperatures are 50°F or higher. For best waterproofing results, wait for a dry (rain-free) period before application. Apply DRYLOK Masonry Waterproofer directly on bare masonry. Apply first coat with a DRYLOK BRUSH or good quality nylon bristle or fiber brush, working the Waterproofer into the pores of the masonry (see COVERAGE). APPLY TWO COATS. Allow 12 hours drying time between coats. The second coat may be applied by brush, roller or spray. For information on spray application, write UGL and ask for Spray Specification Sheet D-30 or visit [www.ugl.com](http://www.ugl.com).

### IMPORTANT

If leaking is still present after two coats, it indicates that pores or pin holes are still open. Paint these areas again. When painting the inside of concrete fish ponds and non-potable water tanks, allow Oil Base DRYLOK Masonry Waterproofer to dry at least one week, fill with water, then drain and refill to control alkalinity content before putting into service.

### VENTILATION

Use an exhaust fan with an explosion-proof motor and non-sparking tips to provide adequate air flow and ventilation.

Keep flow of fresh air until all vapors (odors) are gone. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's direction for respirator use. If cross ventilation is not possible, use Latex Base DRYLOK Masonry Waterproofer, DRYLOK Extreme Waterproofer or DRYLOK Powdered Masonry Waterproofer.

### CAUTION

CONTAINS: PORTLAND CEMENT, CRYSTALLINE SILICA AND PETROLEUM DISTILLATES.

Vapor harmful. Close container after each use. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin and throat irritation. Overexposure may cause lung and kidney damage. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may

be harmful or fatal. Keep away from heat and flame. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Contains Crystalline Silica which can cause cancer. (Risk of cancer depends on duration and level of exposure.)

**Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

**WARNING:** This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

### FIRST AID

**EYES:** Flush immediately with large amounts of water for at least 15 minutes. Consult a physician.

**SKIN:** Wash affected areas with soap and water. Remove contaminated clothing. Consult a physician if irritation persists.

**INGESTION:** Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Consult a physician or poison control center immediately. Treat symptomatically.

**INHALATION:** Remove to fresh air, restore breathing. Treat symptomatically. Consult a physician.

For additional health and safety information please refer to the "Safety Data Sheet".

### WARRANTY

**United Gilsonite Laboratories (UGL®) warrants DRYLOK® Oil Base Masonry Waterproofer**, when applied according to directions on a properly prepared bare masonry surface, will provide a waterproof coating for ten (10) years from the date of application, warranty includes subsequent owners. There are no other warranties that extend beyond this warranty. This warranty shall not apply when the waterproofer fails due to improper product application, failure to follow label directions, inadequate surface preparation, cracked structural surfaces, reoccurring efflorescence or any conditions not

foreseen by UGL. Two coats of DRYLOK Oil Base Waterproofer are required to assure warranted waterproofing. Label directions are as complete as possible, but cannot encompass all conditions, applications and/or surfaces. In the event that the coating fails, your remedy is limited to either replacement of the product purchased or refund of the purchase price. This is the exclusive remedy. For warranty fulfillment, return used product container and sales receipt to UGL, Technical Customer Service, 1396 Jefferson Ave., Dunmore, PA, 18509. **THIS LIMITED WARRANTY EXCLUDES ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE.** UGL will in no event be liable for any incidental or consequential damages. Some States do not allow limitations on how long an implied warranty lasts or the exclusion or limitations of incident or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from State to State.

### SPECIFICATION

TT-C-555B Meets New York Local Law 49; Phila. and PA. Reg. V.

Meets performance of Federal Specification TT-P-1411A, Paint, Copolymer Resin, Cementitious (for waterproofing concrete and masonry walls). Section 4.4.7, Resistance to Wind-Driven Rain of Federal Specification.

Oil Base DRYLOK has been tested to ASTM D-7088 Resistance to Hydrostatic Pressure and ASTM D-6904 Resistance to Wind Driven Rain.



**Oil Base Waterproofer  
Ready Mixed Colors\***

1 GAL.\* 2/Case .....20713  
5 GAL.\* 1/Case .....20715



**White**  
.....20713



**Gray**  
20813  
20815



**Beige**  
21013  
n/a

\* Not available in California \* Regionally VOC restricted

**DISCLAIMER:** This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.