

## PRODUCT DATA SHEET

# DRYLOK® Masonry Crack Filler

Siliconized acrylic latex masonry crack filler

### DESCRIPTION

DRYLOK® Masonry Crack Filler is a superior, fast setting, ready-to-use acrylic fortified silicone caulk. DRYLOK® Masonry Crack Filler seals and waterproofs cracks in interior and exterior concrete walls, walkways, steps, driveways, garage and basement floors, and can be used to replace cracked mortar joints

### USES

Sealing/waterproofing cracks in:

- concrete walls
- walkways / steps / driveways
- garage & basements floors
- mortar joints

### CHARACTERISTICS / ADVANTAGES

- Siliconized acrylic latex formula creates a flexible bond
- Excellent adhesion even to damp surfaces
- Paintable after 1 hour with latex paints
- Fills horizontal and vertical cracks
- Reduces radon gas penetration
- Dries to the color of concrete
- Fast, easy water clean up
- Will not bleed
- Interior/exterior use

#### PRODUCT DATA SHEET

DRYLOK® Masonry Crack Filler

August 2025, Version 01.02

021840303000000054

# PRODUCT INFORMATION

Composition	Acrylic fortified with silicone				
Packaging	Size	PC/Case	Color	Order No.	Old Order No.
	10.5 fl.oz.	10	Gray	773239	30507
Color	Gray				
Shelf life	2 years in unopen container				
Storage conditions	Store between 50° F (10°C) and 85°F (29°C). Protect from freezing.				
Density	13.4 (LBS./US GAL.)				
pH-Value	7.5				
Solid content by mass	83%				

# APPLICATION INFORMATION

Coverage	48 Linear ft. per 1/4” bead
	Note: Actual coverage will vary depending upon application method, surface texture, and porosity.
Ambient air temperature	above 50°F (10°C)
Curing time	12 hours <ul style="list-style-type: none"><li>▪ May be subjected to traffic in 2 hours</li><li>▪ Paintable in 1 hour with latex paint</li></ul>
	Note: Maximum cure and dry time will be prolonged when slightly humid or when damp, cool conditions prevail.

## BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

## LIMITATIONS

- Do not apply in extreme dampness or high humidity
- Do not store in areas of extreme heat or cold
- Not to be used as a substitute for high temperature furnace cement or fireplace mortar
- Not recommended for use under water in concrete pools, fish ponds, etc.



## ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

## APPLICATION INSTRUCTIONS

### SURFACE PREPARATION

Repair area must be free from frost, dust, dirt, oil, and loose particles. The use of a hose and wire brush are effective means of cleaning. Remove any excess moisture or standing water before proceeding with application.

### APPLICATION

Apply product only when air and surface temperatures are above 50°F (10°C). Place the cartridge in any standard caulk gun. Cut the end of plastic spout at 45° angle to desired opening size. Force sealant tightly into crack. Use only in cracks 1/2" (12mm) wide or less. Deep cracks over 1/4" (6mm) should be filled with backing material, such as Sika® Backer Rod, to within 1/4" (6mm) of surface before filling with DRYLOK® Masonry Crack Filler. Smooth the repair with a wet putty knife or trowel.

### CLEANING OF EQUIPMENT

Soap and water. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [www.drylok.com](http://www.drylok.com) or by calling SIKA's Technical Service Department at 1-800-272-3235. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/about-us/terms-conditions-of-sale.html> or by calling 1-800-272-3235.

PRODUCT DATA SHEET  
DRYLOK® Masonry Crack  
Filler

August 2025, Version  
01.02

021840303000000054

3 / 3

**DRYLOK®**

**BUILDING TRUST**



DRYLOKMasonryCrackFiller-en-USDRYLOK-(08-2025)-1-2.pdf