

## PRODUCT DATA SHEET

# DRYLOK® Siloxane 7

### Brick & Masonry Penetrating Sealer

#### DESCRIPTION

DRYLOK® Siloxane 7 Brick & Masonry Penetrating Sealer is a clear, durable, water-repellent, specialty formulation for use on exterior, above-grade, vertical and horizontal brick and masonry surfaces. With just one coat, it minimizes the deterioration of masonry and mortar, and helps control efflorescence (salt deposits) and surface staining.

#### USES

Ideal for use on:

- Vertical and horizontal exterior surfaces
- Brick
- Concrete
- Stucco
- Slate
- Cultured & natural stone

#### CHARACTERISTICS / ADVANTAGES

- Invisible, one-coat weatherproof treatment
- Breathable finish- keeps water out while allowing water vapors to escape
- Contains Silane/Siloxane
- Resists 98 mph wind-driven rain
- Superior performance & protection against staining & efflorescence
- Freeze/Thaw resistant
- Long service life- estimated greater than 10 years
- Non-yellowing

#### PRODUCT DATA SHEET

DRYLOK® Siloxane 7

May 2026, Version 01.03

02189010000000208

## PRODUCT INFORMATION

Composition	Silane/Siloxane				
Packaging	<b>Size</b>	<b>PC/Case</b>	<b>Color</b>	<b>Order No.</b>	<b>Old Order No.</b>
	5 gal.	1	Transparent	832348	23615
	1 gal.	2	Transparent	832347	23613
Shelf life	2 years in unopened container				
Storage conditions	Store between 50° F (10°C) and 85°F (29°C). Extreme heat or freezing temperatures can damage the product, causing it to separate or thicken. Avoid freezing. Keep away from direct sunlight.				
Density	22.5 ± 0.3 lbs./US gal. (S.G. 2.69 ± 0.02)				
Viscosity	11 seconds Ford #4 cup @ 75°F				
Solid content by mass	+7% ± 2				
CSI / CSC MasterFormat®	07 19 00 Water repellents				
Appearance	Transparent				

## TECHNICAL INFORMATION

Resistance to Wind-Driven Rain	98 mph wind-driven rain
--------------------------------	-------------------------

## APPLICATION INFORMATION

Coverage	210 sq. ft./gal. <b>Note:</b> Actual coverage will vary depending upon application method, surface texture, and porosity.
Layer thickness	Flood to the point of rejection
Ambient air temperature	50°F (10°C) or higher
Substrate temperature	50°F (10°C) or higher
Drying time	30 Minutes  <b>Note:</b> Maximum cure and dry time will be prolonged when slightly humid and damp, cool conditions prevail.

PRODUCT DATA SHEET  
DRYLOK® Siloxane 7  
May 2026, Version 01.03  
02189010000000208

**DRYLOK®**

**BUILDING TRUST**



## BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

## SPECIFICATION INFORMATION

- Conforms to ASTM D6904, Resistance to Wind-Driven Rain.
- Meets performance requirements of Federal Specification TT-C555B, PAR 3.3.3, Resistance to Wind-Driven Rain.

## LIMITATIONS

- DO NOT THIN
- Do not apply when temperatures are below 50°F (10°C)
- The product may turn hazy if over-applied (refer to coverage instructions) or if moisture becomes trapped within the substrate. Substrate moisture content must be below 10% before application.

## ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

# APPLICATION INSTRUCTIONS

## EQUIPMENT

Can be applied by:

- Brush
- Roller
- Sprayer

## SUBSTRATE PREPARATION

The surface should be clean, dry, and free from dirt, mildew, and all loose particles. Any previously applied film-forming coating must be removed, and all cracks, holes, and loose mortar joints should be repaired using a suitable concrete patch or mortar mix.

**EFFLORESCENCE**, a white, powdery, crystal-like deposit visible on the masonry surface, must be removed.

Muriatic acid or an acid etch solution, used according to the manufacturer's directions, is an effective efflorescence removal agent. All masonry surfaces are subject to occurrences of efflorescence.

For best results, apply the product when rain is not expected for at least 48 hours. Moisture content must be below 10%.

## APPLICATION

Protect glass, wood surfaces, and shrubbery from overspray. This product will not damage asphalt shingles. The most effective method of application is the use of an ordinary garden pump sprayer. Eliminate most of the pressure at the spray nozzle and operate at the lowest practical pressure on the tank. The nozzle should be opened to a coarse spray adjustment. For even flooding of material, start at the bottom of the wall and hold the spray at an angle to avoid splashing. It is important to hold the spray tip close to the surface to avoid streaking. If DRYLOK® Siloxane 7 is applied with a brush, flow on liberally, do not brush out, to ensure even flooding of the surface. If a second coat is applied, apply wet on wet within 5 minutes. Apply only when air and surface temperatures are 50°F (10°C) or higher.

## CLEANING

Clean using soap and water. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

### PRODUCT DATA SHEET

DRYLOK® Siloxane 7

May 2026, Version 01.03

02189010000000208

**DRYLOK®**

**BUILDING TRUST**



## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at [www.drylok.com](http://www.drylok.com) or by calling SIKA’s Technical Service Department at 1-800-272-3235, option 2. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAM-**

**AGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/about-us/terms-conditions-of-sale.html> or by calling 1-800-272-3235, option 2.

### PRODUCT DATA SHEET

DRYLOK® Siloxane 7

May 2026, Version 01.03

02189010000000208